

# DRAFT

Permit No. **VA0002283**  
Effective Date: **TBD 2013**  
Expiration Date: **TBD 2013**

**AUTHORIZATION TO DISCHARGE UNDER THE  
VIRGINIA POLLUTANT DISCHARGE ELIMINATION SYSTEM  
AND THE VIRGINIA STATE WATER CONTROL LAW**

In compliance with the provisions of the Clean Water Act as amended and pursuant to the State Water Control Law and regulations adopted pursuant thereto, the following owner is authorized to discharge in accordance with the information submitted with the permit application, and with this permit cover page, Part I – Effluent Limitations and Monitoring Requirements, and Part II – Conditions Applicable To All VPDES Permits, and Stormwater Management, as set forth herein.

Owner Name: Motiva Enterprises LLC  
Facility Name: Fairfax Distribution Terminal  
County: Fairfax  
Facility Location: 3800 Pickett Road, Fairfax, VA 22031

The owner is authorized to discharge to the following receiving stream:

Stream Name: Crook Branch  
River Basin: Potomac River  
River Subbasin: None  
Section: 7  
Class: III  
Special Standards: b

---

Thomas A. Faha  
Director, Northern Regional Office  
Department of Environmental Quality

---

Date

**A. Effluent Limitations and Monitoring Requirements****1. Outfall 001 – Stormwater Retention Pond**

- a. There shall be no discharge of floating solids or visible foam in other than trace amounts.
- b. During the period beginning with the permit's effective date and lasting until the expiration date, the permittee is authorized to discharge from Outfall Number 001. Such discharges shall be limited and monitored by the permittee as specified below.

Parameter	Discharge Limitations				Monitoring Requirements	
	<u>Monthly Average</u> <sup>(1)</sup>	<u>Daily Maximum</u> <sup>(1)</sup>	<u>Minimum</u>	<u>Maximum</u> <sup>(1)</sup>	<u>Frequency</u>	<u>Sample Type</u>
Flow (MGD)	NL	NA	NA	NL	1/M	Estimate
pH	NA	NA	6.0 S.U.	9.0 S.U.	1/M	Grab
Total Suspended Solids (TSS)	NA	NA	NA	60 mg/L	1/M	Grab
Total Petroleum Hydrocarbons <sup>(2)</sup>	NA	NA	NA	15 mg/L	1/M	Grab
Naphthalene	NA	NA	NA	8.9 µg/L	1/M	Grab
Zinc, Dissolved <sup>(3)</sup>	NA	NA	NA	NL µg/L	1/Y	Grab
Acute Toxicity <i>C. dubia</i> (NOAEC) <sup>(4)</sup>	NA	NA	NA	NL %	1/Y	Grab

<sup>(1)</sup> See Part I.B.

MGD = Million gallons per day.

1/M = Once every month.

<sup>(2)</sup> Total Petroleum Hydrocarbons (TPH) is the sum of individual gasoline range organics and diesel range organics or TPH-GRO and TPH-DRO to be measured by EPA SW 846 Method 8015 for gasoline and diesel range organics, or by EPA SW 846 Methods 8260 Extended and 8270 Extended.

NA = Not applicable.

1/Y = Once every calendar year.

NL = No limit; monitor and report.

S.U. = Standard units.

<sup>(3)</sup> Sampling results greater than 100 µg/L, the permittee shall investigate and take corrective actions. The permittee shall submit findings and corrective actions to DEQ-NRO within 90 days of the laboratory results.

<sup>(4)</sup> See Part I.E. for Whole Effluent Toxicity monitoring requirements.

Estimate = Reported flow is to be based on the technical evaluation of the sources contributing to the discharge.

Grab = An individual sample collected over a period of time not to exceed 15-minutes.

**2. Outfall 002 – Groundwater Remediation**

- a. There shall be no discharge of floating solids or visible foam in other than trace amounts.
- b. During the period beginning with the permit's effective date and lasting until the expiration date, the permittee is authorized to discharge from Outfall Number 002. Such discharges shall be limited and monitored by the permittee as specified below.

Parameter	Discharge Limitations				Monitoring Requirements	
	<u>Monthly Average</u> <sup>(1)</sup>	<u>Daily Maximum</u> <sup>(1)</sup>	<u>Minimum</u>	<u>Maximum</u> <sup>(1)</sup>	<u>Frequency</u>	<u>Sample Type</u>
Flow (MGD)	NL	NA	NA	NL	Contingent	Estimate
pH	NA	NA	6.0 S.U.	9.0 S.U.	Contingent	Grab
Total Petroleum Hydrocarbons <sup>(2)</sup>	NA	NA	NA	10 mg/L	Contingent	Grab
Benzene	NA	NA	NA	12 µg/L	Contingent	Grab
Ethylbenzene	NA	NA	NA	4.3 µg/L	Contingent	Grab
Toluene	NA	NA	NA	43 µg/L	Contingent	Grab
Total Xylenes	NA	NA	NA	33 µg/L	Contingent	Grab
Naphthalene	NA	NA	NA	8.9 µg/L	Contingent	Grab
Zinc, Total Recoverable	NA	NA	NA	53 µg/L	Contingent	Grab
Chronic Toxicity <i>C. dubia</i> <sup>(3)</sup>	NA	NA	NA	1.8 TU <sub>c</sub>	Contingent	Grab

<sup>(1)</sup> See Part I.B.

<sup>(2)</sup> Total Petroleum Hydrocarbons (TPH) is the sum of individual gasoline range organics and diesel range organics or TPH-GRO and TPH-DRO to be measured by EPA SW 846 Method 8015 for gasoline and diesel range organics, or by EPA SW 846 Methods 8260 Extended and 8270 Extended.

<sup>(3)</sup> See Part I.E. for Whole Effluent Toxicity monitoring requirements.

MGD = Million gallons per day.

NA = Not applicable.

NL = No limit; monitor and report.

S.U. = Standard units.

Contingent = Monitoring only required if a discharge occurs. The reporting frequency shall be semiannual (1/6M).

The semiannual monitoring periods shall be January through June and July through December.

The DMR shall be submitted no later than the 10<sup>th</sup> day of the month following the monitoring period.

Estimate = Reported flow is to be based on the technical evaluation of the sources contributing to the discharge.

Grab = An individual sample collected over a period of time not to exceed 15-minutes.

## B. Quantification Levels and Compliance Reporting

### 1. Quantification Levels

- a. The quantification levels (QL) shall be less than or equal to the following concentrations:

<u>Characteristic</u>	<u>Quantification Level</u>
Total Petroleum Hydrocarbons (TPH)	1.0 mg/L
Zinc, Total Recoverable	42 µg/L

- b. The QL is defined as the lowest concentration used to calibrate a measurement system in accordance with the procedures published for the method. The permittee shall use any method in accordance with Part II A of this permit.
- c. It is the responsibility of the permittee to ensure that proper quality assurance/quality control (QA/QC) protocols are followed during the sampling and analytical procedures. QA/QC information shall be documented to confirm that appropriate analytical procedures have been used and the required QLs have been attained.

### 2. Compliance Reporting for parameters in Part I.A.

- a. Monthly Average – Compliance with the monthly average limitations and/or reporting requirements for the parameters listed in Part I.B.1.a of this permit condition shall be determined as follows: All concentration data below the QL used for the analysis (QL must be less than or equal to the QL listed in Part I.B.1.a above) shall be treated as zero. All concentration data equal to or above the QL used for the analysis (QL must be less than or equal to the QL listed in Part I.B.1.a above) shall be treated as it is reported. An arithmetic average shall be calculated using all reported data for the month, including the defined zeros. This arithmetic average shall be reported on the Discharge Monitoring Report (DMR) as calculated. If all data are below the QL used for the analysis (QL must be less than or equal to the QL listed in Part I.B.1.a above), then the average shall be reported as "< QL". If reporting for quantity is required on the DMR and the reported monthly average concentration is < QL, then report "< QL" for the quantity. Otherwise use the reported concentration data (including the defined zeros) and flow data for each sample day to determine the daily quantity and report the monthly average of the calculated daily quantities.
- b. Daily Maximum – Compliance with the daily maximum limitations and/or reporting requirements for the parameters listed in Part I.B.1.a of this permit condition shall be determined as follows: All concentration data below the QL used for the analysis (QL must be less than or equal to the QL listed in Part I.B.1.a above) shall be treated as zero. All concentration data equal to or above the QL used for the analysis (QL must be less than or equal to the QL listed in Part I.B.1.a above) shall be treated as reported. An arithmetic average shall be calculated using all reported data, including the defined zeros, collected within each day during the reporting month. The maximum value of these daily averages thus determined shall be reported on the DMR as the Daily Maximum. If all data are below the QL used for the analysis (QL must be less than or equal to the QL listed in Part I.B.1.a above), then the maximum value of the daily averages shall be reported as "< QL". If reporting for quantity is required on the DMR and the reported daily maximum is < QL, then report "< QL" for the quantity. Otherwise use the reported daily average concentrations (including the defined zeros) and corresponding daily flows to determine daily average quantities and report the maximum of the daily average quantities during the reporting month.
- c. Single Datum – Any single datum required shall be reported as "< QL" if it is less than the QL used in the analysis (QL must be less than or equal to the QL listed in Part I.B.1.a above). Otherwise the numerical value shall be reported.
- d. Significant Digits – The permittee shall report at least the same number of significant digits as the permit limit for a given parameter. Regardless of the rounding convention used (i.e., 5 always rounding up or to the nearest even number) by the permittee, the permittee shall use the convention consistently, and shall ensure that consulting laboratories employed by the permittee use the same convention.

### C. Stormwater Management Requirements

The existing stormwater pollution prevention plan shall be reviewed and modified, as appropriate, to conform to the requirements of this section. The plan shall identify potential sources of pollution that may reasonably be expected to affect the quality of stormwater discharges associated with industrial activity from the facility. In addition, the plan shall describe and ensure the implementation of practices that are to be utilized to reduce the pollutants in stormwater discharges associated with industrial activity at the facility and to assure compliance with the terms and conditions of this permit. Permittees must implement the provisions of the stormwater pollution prevention plan as a condition of this permit.

The stormwater pollution prevention plan requirements of this permit may be fulfilled by incorporating by reference other plans or documents such as an erosion and sediment control plan, a spill prevention control and countermeasure (SPCC) plan developed for the facility under Section 311 of the Clean Water Act or best management practices (BMP) programs otherwise required for the facility provided that the incorporated plan meets or exceeds the plan requirements of Part I.C. If an erosion and sediment control plan is being incorporated by reference, it shall have been approved by the locality in which the activity is to occur or by another appropriate plan approving authority authorized under the Virginia Erosion and Sediment Control Regulation 4VAC50-30-10 et seq. All plans incorporated by reference into the stormwater pollution prevention plan become enforceable under this permit.

The contents of the SWPPP shall comply with the requirements listed below. The plan shall include, at a minimum, the following items:

#### 1. Pollution Prevention Team

The plan shall identify the staff individuals by name or titles that comprise the facility's stormwater pollution prevention team. The pollution prevention team is responsible for assisting the facility or plant manager in developing, implementing, maintaining, revising and ensuring compliance with the facility's SWPPP. Specific responsibilities of each staff individual on the team shall be identified and listed.

#### 2. Site Description

The plan shall include the following:

- a. Activities at the Facility. A description of the nature of the industrial activities at the facility.
- b. General Location Map. A general location map (e.g., USGS quadrangle or other map) with enough detail to identify the location of the facility and the receiving waters within one mile of the facility.
- c. Site Map. A site map identifying the following:
  - 1). The size of the property (in acres);
  - 2). The location and extent of significant structures and impervious surfaces (roofs, paved areas and other impervious areas);
  - 3). Locations of all stormwater conveyances including ditches, pipes, swales and inlets; including the directions of stormwater flow (use arrows to show which ways stormwater will flow);
  - 4). Locations of all existing structural and source control BMPs;
  - 5). Locations of all surface water bodies, including wetlands;
  - 6). Locations of potential pollutant sources identified under Part I.C.3.;
  - 7). Locations where significant spills or leaks identified under Part I.C.4. have occurred;

- 8). Locations of the following activities where such activities are exposed to precipitation: fueling stations; vehicle and equipment maintenance and/or cleaning areas; loading/unloading areas; locations used for the treatment, storage or disposal of wastes; liquid storage tanks; processing and storage areas; access roads, rail cars and tracks; transfer areas for substances in bulk; and machinery;
  - 9). Locations of stormwater outfalls and an approximate outline of the area draining to each outfall and location of municipal storm sewer systems, if the stormwater from the facility discharges to them;
  - 10). Location and description of all non-storm water discharges;
  - 11). Location of any storage piles containing salt used for deicing or other commercial or industrial purposes; and
  - 12). Locations and sources of runoff to the site from adjacent property, where the runoff contains significant quantities of pollutants. The permittee shall include an evaluation with the SWPPP of how the quality of the stormwater running onto the facility impacts the facility's stormwater discharges.
- d. Receiving Waters and Wetlands. The name of all surface waters receiving discharges from the site, including intermittent streams, dry sloughs and arroyos. Provide a description of wetland sites that may receive discharges from the facility. If the facility discharges through a municipal separate storm sewer system (MS4), identify the MS4 operator and the receiving water to which the MS4 discharges.

### 3. Summary of Potential Pollutant Sources

The plan shall identify each separate area at the facility where industrial materials or activities are exposed to stormwater. Industrial materials or activities include, but are not limited to: material handling equipment or activities, industrial machinery, raw materials, industrial production and processes, intermediate products, byproducts, final products and waste products. Material handling activities include, but are not limited to: the storage, loading and unloading, transportation, disposal or conveyance of any raw material, intermediate product, final product or waste product. For each separate area identified, the description shall include:

- a. Activities in Area. A list of the activities (e.g., material storage, equipment fueling and cleaning, cutting steel beams); and
- b. Pollutants. A list of the associated pollutant(s) or pollutant constituents (e.g., crankcase oil, zinc, sulfuric acid, cleaning solvents, etc.) for each activity. The pollutant list shall include all significant materials handled, treated, stored or disposed that have been exposed to stormwater in the three years prior to the date this SWPPP was prepared or amended. The list shall include any hazardous substances or oil at the facility.

### 4. Spills and Leaks

The SWPPP shall clearly identify areas where potential spills and leaks that can contribute pollutants to stormwater discharges can occur and their corresponding outfalls. The plan shall include a list of significant spills and leaks of toxic or hazardous pollutants that actually occurred at exposed areas or that drained to a stormwater conveyance during the three-year period prior to the date this SWPPP was prepared or amended. The list shall be updated if significant spills or leaks occur in exposed areas of the facility during the term of the permit. Significant spills and leaks include releases of oil or hazardous substances in excess of reportable quantities and may also include releases of oil or hazardous substances that are not in excess of reporting requirements.

### 5. Sampling Data

The plan shall include a summary of existing stormwater discharge sampling data taken at the facility. The summary shall include, at a minimum, any data collected during the previous permit term.

### 6. Stormwater Controls

- a. BMPs shall be implemented for all the areas identified in Part I.C.3. (Summary of Potential Pollutant Sources) to prevent or control pollutants in stormwater discharges from the facility. All reasonable steps shall be taken to control or address the quality of discharges from the site that may not originate at the facility.

The SWPPP shall describe the type, location and implementation of all BMPs for each area where industrial materials or activities are exposed to stormwater. Selection of BMPs shall take into consideration:

- 1). That preventing stormwater from coming into contact with polluting materials is generally more effective, and less costly, than trying to remove pollutants from stormwater;
  - 2). BMPs generally shall be used in combination with each other for most effective water quality protection;
  - 3). Assessing the type and quantity of pollutants, including their potential to impact receiving water quality, is critical to designing effective control measures;
  - 4). That minimizing impervious areas at the facility can reduce runoff and improve groundwater recharge and stream base flows in local streams (however, care must be taken to avoid groundwater contamination);
  - 5). Flow attenuation by use of open vegetated swales and natural depressions can reduce instream impacts of erosive flows;
  - 6). Conservation or restoration of riparian buffers will help protect streams from stormwater runoff and improve water quality; and
  - 7). Treatment interceptors (e.g., swirl separators and sand filters) may be appropriate in some instances to minimize the discharge of pollutants.
- b. Control Measures. The permittee shall implement the following types of BMPs to prevent and control pollutants in the stormwater discharges from the facility, unless it can be demonstrated and documented that such controls are not relevant to the discharges (e.g., there are no storage piles containing salt).
- 1). Good Housekeeping. The permittee shall keep clean all exposed areas of the facility that are potential sources of pollutants to stormwater discharges. Typical problem areas include areas around trash containers, storage areas, loading docks and vehicle fueling and maintenance areas. The plan shall include a schedule for regular pickup and disposal of waste materials, along with routine inspections for leaks and conditions of drums, tanks and containers. The introduction of raw, final or waste materials to exposed areas of the facility shall be minimized to the maximum extent practicable. The generation of dust, along with off-site vehicle tracking of raw, final or waste materials or sediments, shall be minimized to the maximum extent practicable.
  - 2). Eliminating and Minimizing Exposure. To the extent practicable, industrial materials and activities shall be located inside, or protected by a storm-resistant covering to prevent exposure to rain, snow, snowmelt and runoff. Note: Eliminating exposure at all industrial areas may make the facility eligible for the "Conditional Exclusion for No Exposure" provision of 9VAC25-31-120.E, thereby eliminating the need to have a permit.
  - 3). Preventive Maintenance. The permittee shall have a preventive maintenance program that includes regular inspection, testing, maintenance and repairing of all industrial equipment and systems to avoid breakdowns or failures that could result in leaks, spill and other releases. This program is in addition to the specific BMP maintenance required under Part I.C.7. (Maintenance of BMPs).
  - 4). Spill Prevention and Response Procedures. The plan shall describe the procedures that will be followed for preventing and responding to spills and leaks.
    - a) Preventive measures include barriers between material storage and traffic areas, secondary containment provisions and procedures for material storage and handling.
    - b) Response procedures shall include notification of appropriate facility personnel, emergency agencies and regulatory agencies and procedures for stopping, containing and cleaning up spills. Measures for cleaning up hazardous material spills or leaks shall be consistent with applicable RCRA regulations at 40 CFR Part 264 and 40 CFR Part 265. Employees who may cause, detect or respond to a spill or leak shall be trained in these procedures and have necessary spill response equipment available. If possible, one of these individuals shall be a member of the Pollution Prevention Team.

- c) Contact information for individuals and agencies that must be notified in the event of a spill shall be included in the SWPPP and in other locations where it will be readily available.
- 5). Routine Facility Inspections. Facility personnel who possess the knowledge and skills to assess conditions and activities that could impact stormwater quality at the facility and who can also evaluate the effectiveness of BMPs shall regularly inspect all areas of the facility where industrial materials or activities are exposed to stormwater. These inspections are in addition to, or as part of, the comprehensive site evaluation required under Part I.C.8. At least one member of the Pollution Prevention Team shall participate in the routine facility inspections.

The inspection frequency shall be specified in the plan based upon a consideration of the level of industrial activity at the facility, but shall be a minimum of quarterly unless more frequent intervals are specified elsewhere in the permit or written approval is received from the Department for less frequent intervals. At least once each calendar year, the routine facility inspection must be conducted during a period when a stormwater discharge is occurring.

Any deficiencies in the implementation of the SWPPP that are found shall be corrected as soon as practicable, but not later than within 30 days of the inspection unless permission for a later date is granted in writing by the Director. The results of the inspections shall be documented in the SWPPP, along with the date(s) and description(s) of any corrective actions that were taken in response to any deficiencies or opportunities for improvement that were identified.

- 6). Employee Training. The permittee shall implement a stormwater employee training program for the facility. The SWPPP shall include a schedule for all types of necessary training and shall document all training sessions and the employees who received the training. Training shall be provided for all employees who work in areas where industrial materials or activities are exposed to stormwater and for employees who are responsible for implementing activities identified in the SWPPP (e.g., inspectors, maintenance personnel, etc.). The training shall cover the components and goals of the SWPPP and include such topics as spill response, good housekeeping, material management practices, BMP operation and maintenance etc. The SWPPP shall include a summary of any training performed.
- 7). Sediment and Erosion Control. The plan shall identify areas at the facility that, due to topography, land disturbance (e.g., construction, landscaping, site grading) or other factors, have a potential for soil erosion. The permittee shall identify and implement structural, vegetative and/or stabilization BMPs to prevent or control onsite and offsite erosion and sedimentation. Flow velocity dissipation devices shall be placed at discharge locations and along the length of any outfall channel if the flows would otherwise create erosive conditions.
- 8). Management of Runoff. The plan shall describe the stormwater runoff management practices (i.e., permanent structural BMPs) for the facility. These types of BMPs are typically used to divert, infiltrate, reuse or otherwise reduce pollutants in storm water discharges from the site. Structural BMPs may require a separate permit under § 404 of the CWA and the Virginia Water Protection Permit Program Regulation (9VAC25-210) before installation begins.

## 7. Maintenance

All BMPs identified in the SWPPP shall be maintained in effective operating condition. Stormwater BMPs identified in the SWPPP shall be observed during active operation (i.e., during a stormwater runoff event) to ensure that they are functioning correctly. Where discharge locations are inaccessible, nearby downstream locations shall be observed. The observations shall be documented in the SWPPP.

The SWPPP shall include a description of procedures and a regular schedule for preventive maintenance of all BMPs and shall include a description of the back-up practices that are in place should a runoff event occur while a BMP is offline. The effectiveness of nonstructural BMPs shall also be maintained by appropriate means (e.g., spill response supplies available and trained personnel etc.).

If site inspections required by Part I.C.6.b.5 (Routine Facility Inspections) or Part I.C.8 (Comprehensive Site Compliance Evaluation) identify BMPs that are not operating effectively, repairs or maintenance shall be performed before the next anticipated storm event.



If maintenance prior to the next anticipated storm event is not possible, maintenance shall be scheduled and accomplished as soon as practicable. In the interim, backup measures shall be employed and documented in the SWPPP until repairs or maintenance is complete.

Documentation shall be kept with the SWPPP of maintenance and repairs of BMPs, including the date(s) of regular maintenance, date(s) of discovery of areas in need of repair or replacement and for repairs; date(s) that the BMP(s) returned to full function and the justification for any extended maintenance or repair schedules.

#### 8. Comprehensive Site Compliance Evaluation

The permittee shall conduct comprehensive site compliance evaluations at least once a year. The evaluations shall be done by qualified personnel who possess the knowledge and skills to assess conditions and activities that could impact stormwater quality at the facility and who can also evaluate the effectiveness of BMPs. The personnel conducting the evaluations may be either facility employees or outside constituents hired by the facility.

- a. Scope of the Compliance Evaluation. Evaluations shall include all areas where industrial materials or activities are exposed to stormwater, as identified in Part I.C.3. The personnel shall evaluate:
  - 1). Industrial materials, residue or trash that may have or could come into contact with stormwater;
  - 2). Leaks or spills from industrial equipment, drums, barrels, tanks or other containers that have occurred within the past three years;
  - 3). Offsite tracking of industrial or waste materials or sediment where vehicles enter or exit the site;
  - 4). Tracking or blowing of raw, final or waste materials from areas of no exposure to exposed areas;
  - 5). Evidence of, or the potential for, pollutants entering the drainage system;
  - 6). Evidence of pollutants discharging to surface waters at all facility outfalls and the condition of and around the outfall, including flow dissipation measures to prevent scouring;
  - 7). Review of training performed, inspections completed, maintenance performed and effective operation of BMPs;
  - 8). Results any analytical monitoring done during the past year shall be taken into consideration during the evaluation
- b. Based on the results of the evaluation, the SWPPP shall be modified as necessary (e.g., show additional controls on the map required by Part I.C.2.c; revise the description of controls required by Part I.C.6 to include additional or modified BMPs designed to correct problems identified). Revisions to the SWPPP shall be completed within 30 days following the evaluation, unless permission for a later date is granted in writing by the Director. If existing BMPs need to be modified or if additional BMPs are necessary, implementation shall be completed before the next anticipated storm event, if practicable, but not more than 60 days after completion of the comprehensive site evaluation, unless permission for a later date is granted in writing by the Department;
- c. Compliance Evaluation Report. A report shall be written summarizing the scope of the evaluation, name(s) of personnel making the evaluation, the date of the evaluation and all observations relating to the implementation of the SWPPP, including elements stipulated in Part I.C.8.a.1 through Part I.C.8.a.8 above. Observations shall include such things as: the location(s) of discharges of pollutants from the site; location(s) of previously unidentified sources of pollutants; location(s) of BMPs that need to be maintained or repaired; location(s) of failed BMPs that need replacement; and location(s) where additional BMPs are needed. The report shall identify any incidents of noncompliance that were observed. Where a report does not identify any incidents of noncompliance, the report shall contain a certification that the facility is in compliance with the SWPPP and this permit. The report shall be signed in accordance with Part II. K (Signatory Requirements) of this permit and maintained with the SWPPP.
- d. Where compliance evaluation schedules overlap with routine inspections required under Part I.C.6.b.5, the annual compliance evaluation may be used as one of the routine inspections.

9. Signature and Plan Review

- a. **Signature/Location.** The SWPPP shall be signed in accordance with Part II.K (Signatory Requirements) of this permit, dated and retained on-site at the facility covered by this permit in accordance with Part II.B.2 (Records) of this permit. All other changes to the SWPPP, and other permit compliance documentation, must be signed and dated by the person preparing the change or documentation.
- b. **Availability.** The permittee shall make the SWPPP, annual site compliance evaluation report and other information available to the Department upon request.
- c. **Required Modifications.** The Director may notify the permittee at any time that the SWPPP, BMPs or other components of the facility's stormwater program do not meet one or more of the requirements of this permit. The notification shall identify specific provisions of the permit that are not being met, and may include required modifications to the stormwater program, additional monitoring requirements, and special reporting requirements. The permittee shall make any required changes to the SWPPP within 60 days of receipt of such notification, unless permission for a later date is granted in writing by the Director, and shall submit a written certification to the Director that the requested changes have been made.

10. Maintaining an Updated SWPPP

- a. The permittee shall review and amend the SWPPP as appropriate whenever:
  - 1). There is construction or a change in design, operation or maintenance at the facility that has a significant effect on the discharge, or the potential for the discharge, of pollutants from the facility;
  - 2). Routine inspections or compliance evaluations determine that there are deficiencies in the BMPs;
  - 3). Inspections by local, state or federal officials determine that modifications to the SWPPP are necessary;
  - 4). There is a spill, leak or other release at the facility; or
  - 5). There is an unauthorized discharge from the facility.
- b. SWPPP modifications shall be made within 30 calendar days after discovery, observation or event requiring a SWPPP modification. Implementation of new or modified BMPs (distinct from regular preventive maintenance of existing BMPs described in Part I.C.6.b.3) shall be initiated before the next storm event if possible, but no later than 60 days after discovery, or as otherwise provided or approved by the Director. The amount of time taken to modify a BMP or implement additional BMPs shall be documented in the SWPPP.
- c. If the SWPPP modification is based on a release or unauthorized discharge, include a description and date of the release, the circumstances leading to the release, actions taken in response to the release and measures to prevent the recurrence of such releases. Unauthorized releases and discharges are subject to the reporting requirements of Part II.G (Reports of Unauthorized Discharges) of this permit.

**D. Stormwater Pollution Prevention Plan Requirements Specific to Petroleum Bulk Oil Stations and Terminals**

**Discharges Covered Under This Section.** The requirements listed under this section apply to stormwater discharges associated with industrial activity from ground transportation facilities and rail transportation facilities (generally identified by SIC Codes 40, 41, 42, 43, and 5171), that have vehicle and equipment maintenance shops (vehicle and equipment rehabilitation, mechanical repairs, painting, fueling and lubrication) and/or equipment cleaning operations. Also covered under this section are facilities found under SIC Codes 4221 through 4225 (public warehousing and storage) that do not have vehicle and equipment maintenance shops and/or equipment cleaning operations.

In addition to the requirements of Part I.C., the SWPPP shall include, at a minimum, the following items:

1. Site Description

Site Map. The site map shall identify the locations of any of the following activities or sources: fueling stations; vehicle/equipment maintenance or cleaning areas; storage areas for vehicle/equipment with actual or potential fluid leaks; loading/unloading areas; areas where treatment, storage or disposal of wastes occur; liquid storage tanks; processing areas; storage areas; and all monitoring areas.

2. Summary of Potential Pollutant Sources

The plan shall describe and assess the potential for the following to contribute pollutants to stormwater discharges: onsite waste storage or disposal; dirt/gravel parking areas for vehicles awaiting maintenance; and fueling areas.

3. Storm Water Controls

a. Good Housekeeping

- 1). Vehicle and Equipment Storage Areas. The storage of vehicles and equipment awaiting maintenance with actual or potential fluid leaks must be confined to designated areas (delineated on the site map). The permittee shall consider the following measures (or their equivalents): the use of drip pans under vehicles and equipment; indoor storage of vehicles and equipment; installation of berms or dikes; use of absorbents; roofing or covering storage areas; and cleaning pavement surface to remove oil and grease.
- 2). Fueling Areas. The permittee shall describe and implement measures that prevent or minimize contamination of the stormwater runoff from fueling areas. The permittee shall consider the following measures (or their equivalents): covering the fueling area; using spill/overflow protection and cleanup equipment; minimizing stormwater runoff to the fueling area; using dry cleanup methods; and treating and/or recycling collected stormwater runoff.
- 3). Material Storage Areas. Storage vessels of all materials (e.g., for used oil/oil filters, spent solvents, paint wastes, hydraulic fluids) must be maintained in good condition so as to prevent contamination of stormwater and plainly labeled (e.g., "used oil", "spent solvents" etc.). The permittee shall consider the following measures (or their equivalents): indoor storage of the materials; installation of berms/dikes around the areas; minimizing runoff of stormwater to the areas; using dry cleanup methods; and treating and/or recycling the collected stormwater runoff.
- 4). Vehicle and Equipment Cleaning Areas. The permittee shall describe and implement measures that prevent or minimize contamination of stormwater runoff from all areas used for vehicle/equipment cleaning. The permittee shall consider the following measures (or their equivalents): performing all cleaning operations indoors; covering the cleaning operation; ensuring that all washwaters drain to a proper collection system (i.e., not the stormwater drainage system unless VPDES permitted); and treating and/or recycling the collected stormwater runoff. Note: the discharge of vehicle/equipment wash waters, including tank cleaning operations, are not authorized by this permit and must be covered under a separate VPDES permit or discharged to a sanitary sewer in accordance with applicable industrial pretreatment requirements.
- 5). Vehicle and Equipment Maintenance Areas. The permittee shall describe and implement measures that prevent or minimize contamination of the stormwater runoff from all areas used for vehicle/equipment maintenance. The permittee shall consider the following measures (or their equivalents): performing maintenance activities indoors; using drip pans; keeping an organized inventory of materials used in the shop; draining all parts of fluids prior to disposal; prohibiting wet clean up practices where the practices would result in the discharge of pollutants to stormwater drainage systems; using dry cleanup methods; treating and/or recycling collected stormwater runoff; and minimizing runoff of stormwater to maintenance areas.
- 6). Locomotive Sanding (Loading Sand for Traction) Areas. The plan must describe measures that prevent or minimize contamination of the stormwater runoff from areas used for locomotive sanding.

The permittee shall consider the following measures (or their equivalents): covering sanding areas; minimizing stormwater runoff/runoff; or appropriate sediment removal practices to minimize the offsite transport of sanding material by stormwater.

- b. Routine Facility Inspections. The following areas/activities shall be included in all inspections: storage area for vehicles/equipment awaiting maintenance; fueling areas; indoor and outdoor vehicle/equipment maintenance areas; material storage areas; vehicle/equipment cleaning areas; and loading/unloading areas.
- c. Employee Training. Employee training shall take place, at a minimum, annually (once per calendar year). Employee training must address the following, as applicable: used oil and spent solvent management; fueling procedures; general good housekeeping practices; proper painting procedures; and used battery management.
- d. Non-Storm Water Discharges. For facilities that discharge vehicle and equipment washwaters to the sanitary sewer system, the operator of the sanitary system and associated treatment plant must be notified. In such cases, a copy of the notification letter must be attached to the plan. If an industrial user permit is issued under a pretreatment program, a reference to that permit must be in the plan. In all cases, any permit conditions or pretreatment requirements must be considered in the plan. If the washwaters are handled in another manner (e.g., hauled offsite), the disposal method must be described and all pertinent documentation (e.g., frequency, volume, destination, etc.) must be attached to the plan.

#### **E. Whole Effluent Toxicity Program Requirements**

##### **1. Biological Monitoring for Outfall 001**

- a. In accordance with the schedule in Part I.E.2., below, the permittee shall conduct annual acute toxicity tests for the duration of the permit. The permittee shall collect a grab sample of final effluent at Outfall 001.

The acute test to use is:

48 Hour Static Acute test using *Ceriodaphnia dubia*

The acute tests shall be conducted using five (5) geometric dilutions of effluent with a minimum of four (4) replicates, with five (5) organisms in each. The "No Observed Adverse Effect Concentration" (NOAEC) as determined by hypothesis testing shall be reported on the Discharge Monitoring Report (DMR). The  $LC_{50}$  shall also be determined and noted on the submitted report. Tests in which control survival is less than 90% are not acceptable.

- b. The permittee may provide additional samples to address data variability. These data shall be reported. Test procedures and reporting shall be in accordance with the WET testing methods cited in 40 CFR 136.3.
- c. The test dilutions shall be able to determine compliance with the following endpoint:

A NOAEC = 100%

- d. The test data will be evaluated statistically for reasonable potential at the conclusion of the test period. The data may be evaluated sooner if requested by the permittee or if toxicity has been noted. Should evaluation of the data indicate that a limit is warranted, a WET limit and compliance schedule will be required.
- e. The permit may be modified or revoked and reissued to include pollutant specific limits in lieu of a WET limit should it be demonstrated that toxicity is due to specific parameters. The pollutant specific limitations must control the toxicity of the effluent.
- f. The results of the test and the test report shall be reported with the DMR for the month following receipt of the testing results. In no case shall this exceed 45 days from the completion of the test or the submission due dates below, whichever occurs first.

## 2. Reporting Schedule

The permittee shall monitor during the months specified and shall report the results on the DMR and supply a copy of the toxicity test report specified in this Toxics Management Program in accordance with the following schedule:

Period	Sampling Period	DMR/Report Submission Dates
Annual 1	1 January 2014 – 31 December 2014	10 January 2015
Annual 2	1 January 2015 – 31 December 2015	10 January 2016
Annual 3	1 January 2016 – 31 December 2016	10 January 2017
Annual 4	1 January 2017 – 31 December 2017	10 January 2018

## 3. Biological Monitoring for Outfall 002

- a. In accordance with the schedule in Part I.E.4., below, the permittee shall conduct semiannual chronic toxicity tests for the duration of the permit. The permittee shall collect a grab sample of final effluent at Outfall 002.

The chronic test to use is:

Chronic 3-Brood Static Renewal Survival and Reproduction Test using *Ceriodaphnia dubia*

These chronic tests shall be conducted in such a manner and at sufficient dilutions (minimum of five dilutions) to determine the "No Observed Effect Concentration" (NOEC) for survival and reproduction or growth. Results which cannot be quantified (i.e., a "less than" NOEC value) are not acceptable and a retest shall be performed. The NOEC, as determined by hypothesis testing, shall be converted to  $TU_c$  (Chronic Toxic Units) for Discharge Monitoring Report (DMR) reporting where  $TU_c = 100/NOEC$ . Report the  $LC_{50}$  at 48 hours and the  $IC_{25}$  with the NOEC's in the test report.

- b. The permittee may provide additional samples to address data variability. These data shall be reported. Test procedures and reporting shall be in accordance with the WET testing methods cited in 40 CFR 136.3.
- c. The test dilutions shall be able to determine compliance with the WET limitation of 1.8  $TU_c$ .
- d. The results of the test and the test report shall be reported with the DMR for the month following receipt of the testing results. In no case shall this exceed 45 days from the completion of the test or the submission due dates below, whichever occurs first.

## 4. Reporting Schedule

The permittee shall monitor during the months specified and shall report the results on the DMR and supply a copy of the toxicity test report specified in this Toxics Management Program in accordance with the following schedule:

Period	Sampling Period	DMR/Report Submission Dates
Semiannual 1	1 January 2014 – 30 June 2014	10 July 2014
Semiannual 2	1 July 2014 – 31 December 2014	10 January 2015
Semiannual 3	1 January 2015 – 30 June 2015	10 July 2015
Semiannual 4	1 July 2015 – 31 December 2015	10 January 2016
Semiannual 5	1 January 2016 – 30 June 2016	10 July 2016
Semiannual 6	1 July 2016 – 31 December 2016	10 January 2017
Semiannual 7	1 January 2017 – 30 June 2017	10 July 2017
Semiannual 8	1 July 2017 – 31 December 2017	10 January 2018

## **F. Other Requirements and Special Conditions**

### **1. Operation and Maintenance (O&M) Manual Requirement**

The permittee shall maintain a current Operations and Maintenance (O&M) Manual for the treatment works that is in accordance with Virginia Pollutant Discharge Elimination System Regulations, 9VAC25-31.

The O&M Manual and subsequent revisions shall include the manual effective date and meet Part II.K.2 and Part II.K.4 Signatory Requirements of the permit. Any changes in the practices and procedures followed by the permittee shall be documented in the O&M Manual within 90 days of the effective date of the changes. The permittee shall operate the treatment works in accordance with the O&M Manual and shall make the O&M manual available to Department personnel for review during facility inspections. Within 30 days of a request by DEQ, the current O&M Manual shall be submitted to the DEQ-NRO for review and approval.

The O&M Manual shall detail the practices and procedures which will be followed to ensure compliance with the requirements of this permit. This manual shall include, but not necessarily be limited to, the following items, as appropriate:

- a. Permitted outfall locations and techniques to be employed in the collection, preservation and analysis of stormwater discharge;
- b. Procedures for measuring and recording the duration and volume of stormwater discharged;
- c. Discussion of Best Management Practices, if applicable;
- d. Procedures for handling, storing, and disposing of all wastes, fluids and pollutants characterized in Part I.F.3 that will prevent these materials from reaching state waters. List type and quantity of wastes, fluids and pollutants (e.g. chemicals) stored at this facility;
- e. Discussion of oil/water separator design, operation, routine preventative maintenance, critical spare parts inventory and record keeping;
- f. Plan for the management and/or disposal of waste solids and residues;
- g. List of facility, local and state emergency contacts; and
- h. Procedures for reporting and responding to any spills.

### **2. Notification Levels**

The permittee shall notify the Department as soon as they know or have reason to believe:

- a. That any activity has occurred or will occur which would result in the discharge, on a routine or frequent basis, of any toxic pollutant which is not limited in this permit, if that discharge will exceed the highest of the following notification levels:
  - (1) One hundred micrograms per liter;
  - (2) Two hundred micrograms per liter for acrolein and acrylonitrile; five hundred micrograms per liter for 2,4-dinitrophenol and for 2-methyl-4,6-dinitrophenol; and one milligram per liter for antimony;
  - (3) Five times the maximum concentration value reported for that pollutant in the permit application; or
  - (4) The level established by the Board.

- b. That any activity has occurred or will occur which would result in any discharge, on a nonroutine or infrequent basis, of a toxic pollutant, which is not limited in this permit, if that discharge will exceed the highest of the following notification levels:

- (1) Five hundred micrograms per liter;
- (2) One milligram per liter for antimony;
- (3) Ten times the maximum concentration value reported for that pollutant in the permit application; or
- (4) The level established by the Board.

Any and all product, materials, industrial wastes and/or other wastes resulting from the purchase, sale, mining, extraction, transport, preparation and/or storage of raw or intermediate materials, final product, by-product or wastes shall be handled, disposed of and/or stored in such a manner and consistent with Best Management Practices, so as not to permit a discharge of such product, materials, industrial wastes, and/or other wastes to State waters, except as expressly authorized.

3. Materials Handling/Storage

Any and all product, materials, industrial wastes and/or other wastes resulting from the purchase, sale, mining, extraction, transport, preparation and/or storage of raw or intermediate materials, final product, by-product or wastes shall be handled, disposed of and/or stored in such a manner and consistent with Best Management Practices, so as not to permit a discharge of such product, materials, industrial wastes, and/or other wastes to State waters, except as expressly authorized.

4. Oil Storage Ground Water Monitoring Reopener

As this facility currently manages groundwater in accordance with 9 VAC 25-90-10 et seq., Oil Discharge Contingency Plans and Administration Fees for Approval, this permit does not presently impose groundwater monitoring requirements. However, this permit may be modified or alternately revoked and reissued to include groundwater monitoring not required by the ODCP regulation.

5. No Discharge of Detergents, Surfactants or Solvents to Oil-Water Separators

The permittee shall ensure that substances such as detergents, surfactants and solvents do not impact the oil water separators.

6. Total Maximum Daily Load (TMDL) Reopener

This permit shall be modified or alternatively revoked and reissued if any approved wasteload allocation procedure, pursuant to Section 303(d) of the Clean Water Act, imposes wasteload allocations, limits or conditions on the facility that are not consistent with the permit requirements.

CONDITIONS APPLICABLE TO ALL VPDES PERMITS

**A. Monitoring.**

1. Samples and measurements taken as required by this permit shall be representative of the monitored activity.
2. Monitoring shall be conducted according to procedures approved under Title 40 Code of Federal Regulations Part 136 or alternative methods approved by the U.S. Environmental Protection Agency, unless other procedures have been specified in this permit.
3. The permittee shall periodically calibrate and perform maintenance procedures on all monitoring and analytical instrumentation at intervals that will insure accuracy of measurements.
4. Samples taken as required by this permit shall be analyzed in accordance with 1VAC30-45, Certification for Noncommercial Environmental Laboratories, or 1VAC30-46, Accreditation for Commercial Environmental Laboratories.

**B. Records.**

1. Records of monitoring information shall include:
  - a. The date, exact place, and time of sampling or measurements;
  - b. The individual(s) who performed the sampling or measurements;
  - c. The date(s) and time(s) analyses were performed;
  - d. The individual(s) who performed the analyses;
  - e. The analytical techniques or methods used; and
  - f. The results of such analyses.
2. Except for records of monitoring information required by this permit related to the permittee's sewage sludge use and disposal activities, which shall be retained for a period of at least five years, the permittee shall retain records of all monitoring information, including all calibration and maintenance records and all original strip chart recordings for continuous monitoring instrumentation, copies of all reports required by this permit, and records of all data used to complete the application for this permit, for a period of at least 3 years from the date of the sample, measurement, report or application. This period of retention shall be extended automatically during the course of any unresolved litigation regarding the regulated activity or regarding control standards applicable to the permittee, or as requested by the Board.

**C. Reporting Monitoring Results.**

1. The permittee shall submit the results of the monitoring required by this permit not later than the 10th day of the month after monitoring takes place, unless another reporting schedule is specified elsewhere in this permit. Monitoring results shall be submitted to:

Department of Environmental Quality - Northern Regional Office (DEQ-NRO)  
13901 Crown Court  
Woodbridge, VA 22193

Monitoring results shall be reported on a Discharge Monitoring Report (DMR) or on forms provided, approved or specified by the Department.

2. If the permittee monitors any pollutant specifically addressed by this permit more frequently than required by this permit using test procedures approved under Title 40 of the Code of Federal Regulations Part 136 or using other test procedures approved by the U.S. Environmental Protection Agency or using procedures specified in this permit, the results of this monitoring shall be included in the calculation and reporting of the data submitted in the DMR or reporting form specified by the Department.



3. Calculations for all limitations which require averaging of measurements shall utilize an arithmetic mean unless otherwise specified in this permit.

**D. Duty to Provide Information.**

The permittee shall furnish to the Department, within a reasonable time, any information which the Board may request to determine whether cause exists for modifying, revoking and reissuing, or terminating this permit or to determine compliance with this permit. The Board may require the permittee to furnish, upon request, such plans, specifications, and other pertinent information as may be necessary to determine the effect of the wastes from this discharge on the quality of state waters, or such other information as may be necessary to accomplish the purposes of the State Water Control Law. The permittee shall also furnish to the Department upon request, copies of records required to be kept by this permit.

**E. Compliance Schedule Reports.**

Reports of compliance or noncompliance with, or any progress reports on, interim and final requirements contained in any compliance schedule of this permit shall be submitted no later than 14 days following each schedule date.

**F. Unauthorized Discharges.**

Except in compliance with this permit, or another permit issued by the Board, it shall be unlawful for any person to:

1. Discharge into state waters sewage, industrial wastes, other wastes, or any noxious or deleterious substances; or
2. Otherwise alter the physical, chemical or biological properties of such state waters and make them detrimental to the public health, or to animal or aquatic life, or to the use of such waters for domestic or industrial consumption, or for recreation, or for other uses.

**G. Reports of Unauthorized Discharges.**

Any permittee who discharges or causes or allows a discharge of sewage, industrial waste, other wastes or any noxious or deleterious substance into or upon state waters in violation of Part II.F.; or who discharges or causes or allows a discharge that may reasonably be expected to enter state waters in violation of Part II.F., shall notify the Department of the discharge immediately upon discovery of the discharge, but in no case later than 24 hours after said discovery. A written report of the unauthorized discharge shall be submitted to the Department, within five days of discovery of the discharge. The written report shall contain:

1. A description of the nature and location of the discharge;
2. The cause of the discharge;
3. The date on which the discharge occurred;
4. The length of time that the discharge continued;
5. The volume of the discharge;
6. If the discharge is continuing, how long it is expected to continue;
7. If the discharge is continuing, what the expected total volume of the discharge will be; and
8. Any steps planned or taken to reduce, eliminate and prevent a recurrence of the present discharge or any future discharges not authorized by this permit.

Discharges reportable to the Department under the immediate reporting requirements of other regulations are exempted from this requirement.

**H. Reports of Unusual or Extraordinary Discharges.**

If any unusual or extraordinary discharge including a bypass or upset should occur from a treatment works and the discharge enters or could be expected to enter state waters, the permittee shall promptly notify, in no case later than 24 hours, the Department by telephone after the discovery of the discharge. This notification shall provide all available details of the incident, including any adverse affects on aquatic life and the known number of fish killed.

The permittee shall reduce the report to writing and shall submit it to the Department within five days of discovery of the discharge in accordance with Part II.I.2. Unusual and extraordinary discharges include but are not limited to any discharge resulting from:

1. Unusual spillage of materials resulting directly or indirectly from processing operations;
2. Breakdown of processing or accessory equipment;
3. Failure or taking out of service some or all of the treatment works; and
4. Flooding or other acts of nature.

**I. Reports of Noncompliance.**

The permittee shall report any noncompliance which may adversely affect state waters or may endanger public health.

1. An oral report shall be provided within 24 hours from the time the permittee becomes aware of the circumstances. The following shall be included as information which shall be reported within 24 hours under this paragraph:
  - a. Any unanticipated bypass; and
  - b. Any upset which causes a discharge to surface waters.
2. A written report shall be submitted within 5 days and shall contain:
  - a. A description of the noncompliance and its cause;
  - b. The period of noncompliance, including exact dates and times, and if the noncompliance has not been corrected, the anticipated time it is expected to continue; and
  - c. Steps taken or planned to reduce, eliminate, and prevent reoccurrence of the noncompliance.

The Board may waive the written report on a case-by-case basis for reports of noncompliance under Part II.I. if the oral report has been received within 24 hours and no adverse impact on state waters has been reported.

3. The permittee shall report all instances of noncompliance not reported under Parts II, I.1. or I.2., in writing, at the time the next monitoring reports are submitted. The reports shall contain the information listed in Part II.I.2.

NOTE: The immediate (within 24 hours) reports required in Parts II, G., H. and I. may be made to the Department's Northern Regional Office at (703) 583-3800 (voice) or (703) 583-3821 (fax). For reports outside normal working hours, leave a message and this shall fulfill the immediate reporting requirement. For emergencies, the Virginia Department of Emergency Services maintains a 24-hour telephone service at 1-800-468-8892.

**J. Notice of Planned Changes.**

1. The permittee shall give notice to the Department as soon as possible of any planned physical alterations or additions to the permitted facility. Notice is required only when:
  - a. The permittee plans alteration or addition to any building, structure, facility, or installation from which there is or may be a discharge of pollutants, the construction of which commenced:
    - 1) After promulgation of standards of performance under Section 306 of Clean Water Act which are applicable to such source; or

- 2) After proposal of standards of performance in accordance with Section 306 of Clean Water Act which are applicable to such source, but only if the standards are promulgated in accordance with Section 306 within 120 days of their proposal;
  - b. The alteration or addition could significantly change the nature or increase the quantity of pollutants discharged. This notification applies to pollutants which are subject neither to effluent limitations nor to notification requirements specified elsewhere in this permit; or
  - c. The alteration or addition results in a significant change in the permittee's sludge use or disposal practices, and such alteration, addition, or change may justify the application of permit conditions that are different from or absent in the existing permit, including notification of additional use or disposal sites not reported during the permit application process or not reported pursuant to an approved land application plan.
2. The permittee shall give advance notice to the Department of any planned changes in the permitted facility or activity which may result in noncompliance with permit requirements.

#### K. Signatory Requirements.

1. All permit applications shall be signed as follows:
  - a. For a corporation: by a responsible corporate officer. For the purpose of this section, a responsible corporate officer means:
    - 1) A president, secretary, treasurer, or vice-president of the corporation in charge of a principal business function, or any other person who performs similar policy- or decision-making functions for the corporation, or
    - 2) The manager of one or more manufacturing, production, or operating facilities employing more than 250 persons or having gross annual sales or expenditures exceeding \$25 million (in second-quarter 1980 dollars), if authority to sign documents has been assigned or delegated to the manager in accordance with corporate procedures;
  - b. For a partnership or sole proprietorship: by a general partner or the proprietor, respectively; or
  - c. For a municipality, state, federal, or other public agency: by either a principal executive officer or ranking elected official. For purposes of this section, a principal executive officer of a public agency includes:
    - 1) The chief executive officer of the agency, or
    - 2) A senior executive officer having responsibility for the overall operations of a principal geographic unit of the agency.
2. All reports required by permits, and other information requested by the Board shall be signed by a person described in Part II.K.1., or by a duly authorized representative of that person. A person is a duly authorized representative only if:
  - a. The authorization is made in writing by a person described in Part II.K.1.;
  - b. The authorization specifies either an individual or a position having responsibility for the overall operation of the regulated facility or activity such as the position of plant manager, operator of a well or a well field, superintendent, position of equivalent responsibility, or an individual or position having overall responsibility for environmental matters for the company. (A duly authorized representative may thus be either a named individual or any individual occupying a named position.); and
  - c. The written authorization is submitted to the Department.

3. Changes to authorization. If an authorization under Part II.K.2. is no longer accurate because a different individual or position has responsibility for the overall operation of the facility, a new authorization satisfying the requirements of Part II.K.2. shall be submitted to the Department prior to or together with any reports, or information to be signed by an authorized representative.
4. Certification. Any person signing a document under Parts II, K.1. or K.2. shall make the following certification:

"I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system, or those persons directly responsible for gathering the information, the information submitted is, to the best of my knowledge and belief, true, accurate, and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations."

**L. Duty to Comply.**

The permittee shall comply with all conditions of this permit. Any permit noncompliance constitutes a violation of the State Water Control Law and the Clean Water Act, except that noncompliance with certain provisions of this permit may constitute a violation of the State Water Control Law but not the Clean Water Act. Permit noncompliance is grounds for enforcement action; for permit termination, revocation and reissuance, or modification; or denial of a permit renewal application.

The permittee shall comply with effluent standards or prohibitions established under Section 307(a) of the Clean Water Act for toxic pollutants and with standards for sewage sludge use or disposal established under Section 405(d) of the Clean Water Act within the time provided in the regulations that establish these standards or prohibitions or standards for sewage sludge use or disposal, even if this permit has not yet been modified to incorporate the requirement.

**M. Duty to Reapply.**

If the permittee wishes to continue an activity regulated by this permit after the expiration date of this permit, the permittee shall apply for and obtain a new permit. All permittees with a currently effective permit shall submit a new application at least 180 days before the expiration date of the existing permit, unless permission for a later date has been granted by the Board. The Board shall not grant permission for applications to be submitted later than the expiration date of the existing permit.

**N. Effect of a Permit.**

This permit does not convey any property rights in either real or personal property or any exclusive privileges, nor does it authorize any injury to private property or invasion of personal rights, or any infringement of federal, state or local law or regulations.

**O. State Law.**

Nothing in this permit shall be construed to preclude the institution of any legal action under, or relieve the permittee from any responsibilities, liabilities, or penalties established pursuant to any other state law or regulation or under authority preserved by Section 510 of the Clean Water Act. Except as provided in permit conditions on "bypassing" (Part II.U.), and "upset" (Part II.V.) nothing in this permit shall be construed to relieve the permittee from civil and criminal penalties for noncompliance.

**P. Oil and Hazardous Substance Liability.**

Nothing in this permit shall be construed to preclude the institution of any legal action or relieve the permittee from any responsibilities, liabilities, or penalties to which the permittee is or may be subject under Sections 62.1-44.34:14 through 62.1-44.34:23 of the State Water Control Law.

**Q. Proper Operation and Maintenance.**

The permittee shall at all times properly operate and maintain all facilities and systems of treatment and control (and related appurtenances) which are installed or used by the permittee to achieve compliance with the conditions of this permit. Proper operation and maintenance also includes effective plant performance, adequate funding, adequate staffing, and adequate laboratory and process controls, including appropriate quality assurance procedures. This provision requires the operation of back-up or auxiliary facilities or similar systems which are installed by the permittee only when the operation is necessary to achieve compliance with the conditions of this permit.

**R. Disposal of solids or sludges.**

Solids, sludges or other pollutants removed in the course of treatment or management of pollutants shall be disposed of in a manner so as to prevent any pollutant from such materials from entering state waters.

**S. Duty to Mitigate.**

The permittee shall take all reasonable steps to minimize or prevent any discharge or sludge use or disposal in violation of this permit which has a reasonable likelihood of adversely affecting human health or the environment.

**T. Need to Halt or Reduce Activity not a Defense.**

It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of this permit.

**U. Bypass.**

1. "Bypass" means the intentional diversion of waste streams from any portion of a treatment facility. The permittee may allow any bypass to occur which does not cause effluent limitations to be exceeded, but only if it also is for essential maintenance to assure efficient operation. These bypasses are not subject to the provisions of Parts II, U.2. and U.3.
2. Notice
  - a. Anticipated bypass. If the permittee knows in advance of the need for a bypass, prior notice shall be submitted, if possible at least ten days before the date of the bypass.
  - b. Unanticipated bypass. The permittee shall submit notice of an unanticipated bypass as required in Part II.I.
3. Prohibition of bypass.
  - a. Bypass is prohibited, and the Board may take enforcement action against a permittee for bypass, unless:
    - 1) Bypass was unavoidable to prevent loss of life, personal injury, or severe property damage;
    - 2) There were no feasible alternatives to the bypass, such as the use of auxiliary treatment facilities, retention of untreated wastes, or maintenance during normal periods of equipment downtime. This condition is not satisfied if adequate back-up equipment should have been installed in the exercise of reasonable engineering judgment to prevent a bypass which occurred during normal periods of equipment downtime or preventive maintenance; and
    - 3) The permittee submitted notices as required under Part II.U.2.
  - b. The Board may approve an anticipated bypass, after considering its adverse effects, if the Board determines that it will meet the three conditions listed above in Part II.U.3.a.

**V. Upset.**

1. An upset constitutes an affirmative defense to an action brought for noncompliance with technology based permit effluent limitations if the requirements of Part II.V.2. are met. A determination made during administrative review of claims that noncompliance was caused by upset, and before an action for noncompliance, is not a final administrative action subject to judicial review.
2. A permittee who wishes to establish the affirmative defense of upset shall demonstrate, through properly signed, contemporaneous operating logs, or other relevant evidence that:
  - a. An upset occurred and that the permittee can identify the cause(s) of the upset;
  - b. The permitted facility was at the time being properly operated;
  - c. The permittee submitted notice of the upset as required in Part II.I.; and
  - d. The permittee complied with any remedial measures required under Part II.S.
3. In any enforcement preceding the permittee seeking to establish the occurrence of an upset has the burden of proof.

**W. Inspection and Entry.**

The permittee shall allow the Director, or an authorized representative, upon presentation of credentials and other documents as may be required by law, to:

1. Enter upon the permittee's premises where a regulated facility or activity is located or conducted, or where records must be kept under the conditions of this permit;
2. Have access to and copy, at reasonable times, any records that must be kept under the conditions of this permit;
3. Inspect at reasonable times any facilities, equipment (including monitoring and control equipment), practices, or operations regulated or required under this permit; and
4. Sample or monitor at reasonable times, for the purposes of assuring permit compliance or as otherwise authorized by the Clean Water Act and the State Water Control Law, any substances or parameters at any location.

For purposes of this section, the time for inspection shall be deemed reasonable during regular business hours, and whenever the facility is discharging. Nothing contained herein shall make an inspection unreasonable during an emergency.

**X. Permit Actions.**

Permits may be modified, revoked and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition.

**Y. Transfer of permits.**

1. Permits are not transferable to any person except after notice to the Department. Except as provided in Part II.Y.2., a permit may be transferred by the permittee to a new owner or operator only if the permit has been modified or revoked and reissued, or a minor modification made, to identify the new permittee and incorporate such other requirements as may be necessary under the State Water Control Law and the Clean Water Act.
2. As an alternative to transfers under Part II.Y.1., this permit may be automatically transferred to a new permittee if:
  - a. The current permittee notifies the Department at least 30 days in advance of the proposed transfer of the title to the facility or property;

- b. The notice includes a written agreement between the existing and new permittees containing a specific date for transfer of permit responsibility, coverage, and liability between them; and
- c. The Board does not notify the existing permittee and the proposed new permittee of its intent to modify or revoke and reissue the permit. If this notice is not received, the transfer is effective on the date specified in the agreement mentioned in Part II.Y.2.b.

**Z. Severability.**

The provisions of this permit are severable, and if any provision of this permit or the application of any provision of this permit to any circumstance is held invalid, the application of such provision to other circumstances, and the remainder of this permit, shall not be affected thereby.